

Depletion Mode MOSFETs

Device	BV _{DSX} min (V)	R _{DS(ON)} max (Ω)	V _{GS(OFF)}		I _{DSS} @ V _{GS} = 0V		Package Options	Application Notes
			min (V)	max (V)	min (mA)	max (mA)		
DN1509	90	6.0	- 1.8	- 3.5	300	-	3-Lead SOT-89 (N8)	-
DN2450	500	10	-1.5	-3.5	700	-	3-Lead TO-252 (K4) 3-Lead SOT-89 (N8)	-
DN2470	700	42	- 1.5	- 3.5	500 (typ)	-	3-Lead TO-252 (K4)	-
DN2530	300	12	- 1.0	- 3.5	200	-	3-Lead TO-92 (N3) 3-Lead SOT-89 (N8)	-
DN2535	350	25	- 1.5	- 3.5	150	-	3-Lead TO-92 (N3) 3-Lead TO-220 (N5)	AN-D30
DN2540	400	25	- 1.5	- 3.5	150	-	3-Lead TO-92 (N3) 3-Lead TO-220 (N5) 3-Lead SOT-89 (N8)	-
DN2625	250	3.5	-1.5	-2.1	3300	-	3-Lead TO-252 (K4)	-
DN3135	350	35	- 1.5	- 3.5	180	-	3-Lead SOT-23 (K1) 3-Lead SOT-89 (N8)	-
DN3145	450	60	- 1.5	- 3.5	120	-	3-Lead SOT-89 (N8)	-
DN3525	250	6.0	- 1.5	- 3.5	300	-	3-Lead SOT-89 (N8)	-
DN3535	350	10	- 1.5	- 3.5	200	-	3-Lead SOT-89 (N8)	-
DN3545	450	20	- 1.5	- 3.5	200	-	3-Lead TO-92 (N3) 3-Lead SOT-89 (N8)	-
DN3765	650	8.0	-1.5	-3.5	200	-	3-Lead TO-252 (K4)	-
LND01	9.0	1.4	-0.8	-3.0	300	-	5-Lead SOT-23 (K1)	-
LND150	500	1000	- 1.0	- 3.0	1.0	3.0	3-Lead SOT-23 (K1) 3-Lead TO-92 (N3) 3-Lead SOT-89 (N8)	AN-D10 AN-D11 AN-D12 AN-D16 AN-D17 AN-D25 AN-D27